
















		<b>RFM</b>	<b>RSV</b>	<b>RSV</b>	<b>SCB</b>
Type of Relay					
LxWxH(mm)		23.0x15.5x26.0	28.0x28.0x30.7	28.8x28.8x26.6	27.0x23.0x41.5
Arrangement		1a, 1c	1a, 1b, 1c, 2au, 2a	1a, 1b, 1c	1a, 1b, 1c, 2au
Contact Current		20A, 25A	40A, 70A	40A, 70A	40A, 70A
Contact Rating		1a 14VDC 25A	40A 14VDC 40A	40A 14VDC 40A	40A: 12VDC 40A
		1a 14VDC 20A	70A 14VDC 70A	70A 14VDC 70A	70A: 14VDC 70A
Coil Voltage	DC	6-48VDC	12-24VDC	12-24VDC	12-24VDC
	AC				
Coil Power	DC	1.2W	1.6W	1.6W	1.2W, 1.6W, 2.0W
	AC				
Insulation Resistance		DC500V 50m $\Omega$	DC500V 50m $\Omega$	DC500V 50m $\Omega$	DC500V 50m $\Omega$
Dielectric Strength		1000VAC	500VAC	500VAC	1000VAC
between coil & contact			500VAC	500VAC	500VAC
between contact		500VAC	500VAC	500VAC	500VAC
Life	Mechanically	$1 \times 10^7$	$1 \times 10^7$	$1 \times 10^7$	$1 \times 10^7$
	Electrically	$1 \times 10^5$	$1 \times 10^5$	$1 \times 10^5$	$1 \times 10^5$
Dimensions (mm)					
					
Terminal Type					
Approval				